

STOCK # **22**
 GRADE II X-TRA
 FULL VACUUM LOAD



P-72

P-72 SAND SUCTION

COMPOUND / SBR - (STYRENE BUTADIENE RUBBER)



TENSILE (PSI)	ELONGATION (%)	MODULUS (300%)	TEMP. RATING	DURO (HARDNESS)	SPEC. GRAVITY
2400	640	1100	-40 / 220°	60 ± 5	1.14

CARCASS / 100% POLYESTER – (PLAIN WEAVE, WARP & FILL)

CONSTRUCTION: HAND BUILT, MANDREL WRAPPED.

COLOR / SERVICE: Black - High Pressure Suction.

TUBE: SBR of 3/8", 1/2", 3/4", 1" Thicknesses.

REINFORCEMENT: Multiple Plies of 110 lb. Polyester Fabric with a 1/4" Hard Drawn Steel Spring Wire Deeply Embedded to Prevent Collapse.

COVER: SBR 1/16" Thick.

PACKAGING: 10' Min. / 30' Max. with Straight Ends.



*BRANDING:



* Factory Stocked in **10'** Lengths by 3/8" & 1/2" Wear Tubes!

PRC ID	3/8" Tube		1/2" Tube		Max. Working Pressure
	PLY	Wt/Ft	OD	Wt/Ft	
4 1/2"	3	6.4	6.3	7.3	250 PSI
6 5/8"	4	10.8	8.7	12.1	225 PSI
8 5/8"	4	16.5	11.1	18.2	200 PSI
10 3/4"	5	22.3	13.4	24.5	175 PSI
12 3/4"	6	28.6	15.6	31.1	150 PSI
14"	7	33.8	17.1	36.5	130 PSI
16"	8	41.3	19.3	44.4	125 PSI
18"	9	49.4	21.5	52.9	125 PSI
20"	10	55.6	23.7	59.1	125 PSI

Price Rubber fully warrants and guarantees all products against material defect and workmanship for the life of the product. PRC Hoses are custom built and precision made. Price uses 100% polyester textiles to give maximum protection against "burst" and will not rot, mildew, or wick moisture! Each & every PRC Hose is custom engineered with a nylon wrapped textured finish for job-matched performance. Experience the Price Advantage . . .

Value that Lasts!



FOR MORE INFORMATION, CONTACT YOUR LOCAL PRICE RUBBER DISTRIBUTOR OR CALL PRC CUSTOMER SERVICE:
 WATTS: (800) 633-1470 • FAX: (334) 271-3194
 www.pricerubber.com