

STOCK # **22**
 GRADE II X-TRA
 FULL VACUUM LOAD

Price Rubber Corp.

P-72

P-72 SAND SUCTION

COMPOUND / SBR - (STYRENE BUTADIENE RUBBER)

TENSILE (PSI)	ELONGATION (%)	MODULUS (300%)	TEMP. RATING	DURO (HARDNESS)	SPEC. GRAVITY
2400	640	1100	-40 / 220°	60 ± 5	1.14

CARCASS / 100% POLYESTER – (PLAIN WEAVE, WARP & FILL)
CONSTRUCTION: HAND BUILT, MANDREL WRAPPED.

COLOR / SERVICE: Black - High Pressure Suction.

TUBE: SBR of 3/8", 1/2", 3/4", 1" Thicknesses.

REINFORCEMENT: Multiple Plies of 110 lb. Polyester Fabric with a 1/4" Hard Drawn Steel Spring Wire Deeply Embedded to Prevent Collapse.

COVER: SBR 1/16" Thick.

PACKAGING: 10' Min. / 30' Max. with Straight Ends.

*BRANDING:

Price RUBBER CORP. P-72 SAND SUCTION 150 psi Made in USA



* Factory Stocked in **10'** Lengths by 3/8" & 1/2" Wear Tubes!

PRC	3/8" Tube		1/2" Tube			Max. Working Pressure
ID	PLY	Wt/Ft	OD	Wt/Ft	OD	
4 1/2"	3	6.4	6.3	7.3	6.6	250 PSI
6 5/8"	4	10.8	8.7	12.1	9.0	225 PSI
8 5/8"	4	16.5	11.1	18.2	11.3	200 PSI
10 3/4"	5	22.3	13.4	24.5	11.6	175 PSI
12 3/4"	6	28.6	15.6	31.1	15.9	150 PSI
14"	7	33.8	17.1	36.5	17.3	130 PSI
16"	8	41.3	19.3	44.4	19.5	125 PSI
18"	9	49.4	21.5	52.9	21.7	125 PSI
20"	10	55.6	23.7	59.1	23.9	125 PSI

Price Rubber Corp.

FOR MORE INFORMATION, CONTACT YOUR LOCAL PRICE RUBBER CUSTOMER SERVICE:

WATTS: 888-778-7707 • FAX: 334-279-5603

www.pricerubber.com