

STOCK # **37**

REFUSE & RECYCLING /
MUNICIPAL DISPOSAL

Price RUBBER CORP.

WASTE TREATMENT

SPECIAL POLYMER BLEND!
PROVIDES MORE OIL RESISTANCE THAN
STANDARD "MOR" BELT GRADES!

COMPOUND / SBR - (*SPECIALLY ENHANCED)

| TENSILE (PSI) | ELONGATION (%) | MODULUS (300%) | TEMP. RATING | DURO (HARDNESS) | SPEC. GRAVITY |
|---------------|----------------|----------------|--------------|-----------------|---------------|
| 2200 | 510 | 1100 | -40 / 220°F. | 65 ± 5 | 1.16 |

CARCASS / 100% POLYESTER – (PLAIN WEAVE, WARP & FILL)

| *11:1 Safety | 2/220 | 3/330 | 4/440 | 3/600 | 3/750 | 4/800 | 4/1000 | 5/1250 |
|------------------------------------|--------|--------|--------|--------|--------|--------|--------|---------|
| Fabric Type | P/P | P/P | P/P | P/P | P/P | P/P | P/P | P/P |
| Vulcanized & Fastener Rating (piw) | 220 | 330 | 440 | 600 | 750 | 800 | 1000 | 1250 |
| Carcass Gauge (in.) | .106 | .159 | .192 | .195 | .252 | .240 | .316 | .380 |
| Carcass Weight (lbs/sq.ft.) | .64 | .95 | 1.15 | 1.17 | 1.51 | 1.44 | 1.90 | 2.28 |
| Approx 1/32 cover wt (lbs/sq.ft.) | .19 | .19 | .19 | .19 | .19 | .19 | .19 | .19 |
| Avg. Permanent Elongation (%) | 1.5% | 1.5% | 1.5% | 1.5% | 1.5% | 1.5% | 1.5% | 1.5% |
| Elastic modulus (piw) | 23,000 | 34,500 | 46,000 | 66,000 | 67,500 | 88,000 | 90,000 | 112,500 |
| Recommended Fastener Plate | 140 | 190 | BR-10 | BR-10 | BR-14 | BR-14 | *NR | *NR |
| Hinge | R2 | R2 | R5 | R5½ | R6 | R6 | RAR8 | RAR8 |

TROUGHABILITY (Minimum Belt Width) (in.)

*VULCANIZE

| | 2/220 | 3/330 | 4/440 | 3/600 | 3/750 | 4/800 | 4/1000 | 5/1250 |
|------------------|-------|-------|-------|-------|-------|-------|--------|--------|
| 20 degree idlers | 18 | 18 | 24 | 24 | 24 | 30 | 30 | 36 |
| 35 degree idlers | 18 | 24 | 30 | 30 | 30 | 36 | 36 | 42 |
| 45 degree idlers | 24 | 30 | 36 | 36 | 36 | 42 | 42 | 48 |

MINIMUM PULLEY DIAMETERS (in.)

| | 2/220 | 3/330 | 4/440 | 3/600 | 3/750 | 4/800 | 4/1000 | 5/1250 |
|--------------------|-------|-------|-------|-------|-------|-------|--------|--------|
| Over 80% Tension | 16 | 18 | 24 | 24 | 30 | 30 | 36 | 42 |
| 60% to 80% Tension | 14 | 16 | 20 | 20 | 24 | 24 | 30 | 36 |

LOAD SUPPORT (Maximum Belt Width) (in.)

| | 2/220 | 3/330 | 4/440 | 3/600 | 3/750 | 4/800 | 4/1000 | 5/1250 |
|---------------------|-------|-------|-------|-------|-------|-------|--------|--------|
| 0 - 40 lbs/cu.ft. | 42 | 54 | 60 | 72 | 72 | 84 | 84 | 108 |
| 41 - 80 lbs/cu.ft. | 36 | 48 | 60 | 60 | 60 | 72 | 72 | 96 |
| 81 - 120 lbs/cu.ft. | 36 | 48 | 54 | 60 | 60 | 72 | 72 | 96 |
| Over 120 lbs/cu.ft. | 30 | 42 | 48 | 54 | 54 | 60 | 60 | 84 |

Price RUBBER CORP.

FOR MORE INFORMATION, CONTACT YOUR LOCAL PRICE RUBBER CUSTOMER SERVICE:

WATTS: 888-778-7707 • FAX: 334-279-5603

www.pricerubber.com